

Manufacturer	Model	Media	Media Capacity	Media Slots	File Formats	Sampling Rates kHz	Bit Depth bits	Stereo/ Mono	Size inches, wxhxd	Weight pounds (w/o batteries unless noted)	Inputs	Outputs	Power	Extras
Core Sound http://www.core-sound.com														
	PDAudio-CF	PDA recorder hardware	depends on hardware	*	depends on software	32, 44.1, 48, 88.2, 96, 176.4, 192	8, 16, 20, 24	both	*	*	3.5mm TRS, optical S/PDIF and AES-3	*	*	
Denon http://www.usa.denon.com														
	DN-F20R	Compact Flash	2GB	2	MPEG 1, MPEG 2, .WAV	24, 48	16	both	8.2x1.7x6.3	2	2 XLR mic, stereo RCA line	stereo RC line	6 AA batteries, ac adapter	monitor speaker
Digigram http://www.digigram.com														
	RCX220	PCMCIA	any	1	layer II, G.722	16 to 48	16	both	7.5x3.25x1	1	12-pole DIN mic or balanced line		5 AA batteries, 9Vdc, ac adapter	headphone jack, USB, Xtrack LE editor
Fostex http://www.fostexdvd.net														
	FR-2	PCMCIA	any	1	.BWF	22.05, 44.1, 48, 88.2, 96, 176.4, 192	16, 24	both	9.8x3x8.6	3.3	2 XLR mics w/ phantom, AES-3, S/PDIF	stereo RCA line, AES-3, S/PDIF	8 AA batteries, ac adapter, 12Vdc	monitor speaker, headphone jack, USB file transfer
	PD-6	DVD-RAM, internal HD	1.46BG (DVD), 40GB (HD)	1	.BWF	44.1, 48, 88.2, 96	16, 24	up to six tracks	13x4.3x9.5	7.7	6 mic/line XLR, DB25 digital	6 line XLR, DB25 digital	NP-1 battery, ac adapter, 12Vdc to 18Vdc	six-channel mixer, headphone jack, USB, Firewire,

Manufacturer	Model	Media	Media Capacity	Media Slots	File Formats	Sampling Rates kHz	Bit Depth bits	Stereo/ Mono	Size inches, wxhxd	Weight pounds (w/o batteries unless noted)	Inputs	Outputs	Power	Extras
HHB http://www.hbusa.com														
	Portadrive PDR2000	hard drive	40GB	1	.BWF, SDII	44.1, 48, 88.2, 96	16, 24	up to eight tracks	13.1x4.2x8. 8	11.6	6 mic/line XLR, 8- channel AES-3, RCA S/PDIF	dual stereo XLR line, 8- channel AES-31, RCA S/PDIF	NP-1, 12Vdc to 18Vdc, ac adapter	monitor speaker, headphone jack, 10- second pre-record buffer, USB, SCSI, Ethernet, PS2 keyboard
	Portadisc MDP500	MiniDisc	N/A	1	ATRAC	44.1	16	stereo	10x2.2x7.1	4	2 mic/line XLR, TOSLINK and RCA S/PDIF	stereo RCA line, TOSLINK and RCA S/PDIF	8 AA batteries, 12Vdc to 15Vdc	pre-record buffer, monitor speaker, headphone jack, USB
Marantz http://www.d-mpro.com														
	PMD670	Compact Flash	2GB	1	MPEG 1 layer II, MPEG 1 layer III, MPEG 2 layer III, .WAV, .BWF	16, 22.05, 24, 32, 44.1, 48	16	stereo	10.4x2x7.3	2.87	2 mic XLR w/ phantom, stereo RC line, S/PDIF RCA	stereo RCA line, S/PDIF RCA	8 AA batteries, ac adapter, 13Vdc	2-second re-record buffer, monitor speaker, headphone jack, PMDedit software, 15- pin I/O port, USB
	CR300	CD-R, CD- RW	700MB	2	PCM	44.1	16	stereo	11x4x9	7	2 mic/line XLR, 2 mic/line 1/4", RCA S/PDIF, stereo RCA	RCA S/PDIF, dual stereo RCA	external battery, 13.2Vdc, ac power	internal mic, monitor speaker, headphone jack, IR remote control
	PMD221	Cassette	any	1	N/A	N/A	N/A	mono	9x2x6.5	2.9	1/4" mic, 1/8" mic, RCA line	RCA line	3 D batteries, 4.5Vdc, ac adapter	monitor speaker, built- in mic, 3-head
	PMD222	Cassette	any	1	N/A	N/A	N/A	mono	9x2x6.5	2.9	XLR mic, 1/8" mic, RCA line	RCA line	3 D batteries, 4.5Vdc, ac adapter	monitor speaker, built- in mic, 3-head, telco connector

Manufacturer	Model	Media	Media Capacity	Media Slots	File Formats	Sampling Rates kHz	Bit Depth bits	Stereo/Mono	Size inches, w×h×d	Weight pounds (w/o batteries unless noted)	Inputs	Outputs	Power	Extras
Marantz (cont.)	PMD101	Cassette	any	1	N/A	N/A	N/A	mono	9×2×6.5	2.9	1/8" mic, RCA line	RCA line	3 D batteries, 4.5Vdc, ac adapter	monitor speaker, built-in mic, 2-head
	PMD201	Cassette	any	1	N/A	N/A	N/A	mono	9×2×6.5	2.9	1/8" mic, RCA line	RCA line	3 D batteries, 4.5Vdc, ac adapter	monitor speaker, built-in mic, 2-head
Mayah	http://www.mayah.com													
	Flashman	Compact Flash	256MB	1	layer II, Layer III, .BWF	32, 44.1, 48	16	both	5×2.1×5.8	1.3	XLR mic, 3.5mm TRS mic, 3.5mm TRS mic, 3.5mm TRS S/PDIF	3.5mm TRS line, 3.5mm TRS S/PDIF	4 AA batteries, 6Vdc, ac adapter	headphone jack
Maycom	http://www.maycom.nl													
	Easycorder	internal solid-state, PCMCIA slot	any PCMCIA	1	layer II, .BWF, .WAV, .AIFF	11.025 to 48	16	both	7.5×2.4×9.5	5.3 w/ batteries	2 mic/line XLR, cinch S/PDIF	2 XLR line, XLR AES-3, cinch S/PDIF	8 C batteries, 12Vdc to 24Vdc, ac adapter	monitor speaker, headphone jack, editing capability, ISDN connectivity
	Handheld II	Compact Flash	512MB	1	layer II, .BWF	16 to 48	16	both	7×2.5×1.2	0.66 w/ batteries	2 mic/line	2 unbalanced line	4 AAA batteries	monitor speaker, built-in mic, included docking station provides additional features and functions such as USB and XLR connectors

Manufacturer	Model	Media	Media Capacity	Media Slots	File Formats	Sampling Rates kHz	Bit Depth bits	Stereo/ Mono	Size inches, w×h×d	Weight pounds (w/o batteries unless noted)	Inputs	Outputs	Power	Extras
Nagra http://www.nagraaudio.com														
	ARES-P	PCMCIA	any	1	layer II, G.722	16 to 48	16	both	7.5×3.25×1	1	12-pole DIN mic or balanced line		5 AA batteries, 9Vdc, ac adapter	headphone jack
	ARES-P11	PCMCIA	any	1	PCM	16 to 48	16	both	7.5×3.25×1	1	12-pole DIN mic or balanced line		5 AA batteries, 9Vdc, ac adapter	monitor speaker, headphone jack, USB
	ARES-C	PCMCIA	any	1	layer II, G.722, G.711	16 to 48	16	both	11.4×5.6×3.6	6.4 w/ batteries	2 XLR mic, DIN-15 line	AES-3 XLR	4 D batteries, Li-ion battery, 6Vdc to 13.8Vdc, ac adapter	POTS connectivity, built in editor, ISDN connectivity, ARES Import to read cards on a PC,
	ARES-BB	PCMCIA	any	1	layer II, G.722	16 to 48	16	both	6.3×6.6×2.2	2	2 XLR mic		6 AA batteries, 9Vdc, ac adapter	headphone jack, USB

Manufacturer	Model	Media	Media Capacity	Media Slots	File Formats	Sampling Rates kHz	Bit Depth bits	Stereo/ Mono	Size inches, w×h×d	Weight pounds (w/o batteries unless noted)	Inputs	Outputs	Power	Extras
Orban http://www.orban.com														
	Opticodec 7000	PCMCIA	16MB, 32MB, 48MB, 64MB, 80MB	1	layer II, layer III, .BWF, G.722, G.711	32	16	both	6×9.5×2.375	3.2 w/ batteries	2 XLR mic/line	2 XLR mic/line	7.2Vdc LI-ion battery pack, 12Vdc	headphone jack, built-in editor, ISDN connectivity
Pocketrec http://www.pocketrec.com														
	Pocketrec	PDA recorder software	depends on hardware	*	.WAV	8, 11.025, 12, 16, 22.05, 24, 32, 44.1, 48	8, 16	mono	*	*	*	*	*	
Sonifex http://www.sonifex.co.uk														
	Courier	PCMCIA	any	1	layer II, .WAV, .AIFF, Dave2000	8, 11.025, 12, 16, 22.05, 24, 32, 44.1, 48	8, 16	both	9.5×3.1×10.25	3.3 w/ batteries	2 mic/line XLR w/ phantom	2 line XLR, AES-3 XLR	6Vdc 8mm camcorder battery, 6 AA batteries (w/caddy), car power adapter	monitor speaker, headphone jack, POTS and ISDN connectivity
Sony http://bssc.sel.sony.com														
	PCM-M1	DAT	120 mins	1	PCM	32, 44.1, 48	12, 16	stereo	3.15×4.6×1.15	0.64	3.5mm TRS mic/line	7-pin digital	2 AA batteries, 4.5Vdc, ac adapter	headphone jack

Manufacturer	Model	Media	Media Capacity	Media Slots	File Formats	Sampling Rates kHz	Bit Depth bits	Stereo/ Mono	Size inches, w×h×d	Weight pounds (w/o batteries unless noted)	Inputs	Outputs	Power	Extras
Sound Devices http://www.sounddevices.com														
	722	internal HD, PCMCIA	20GB HD	1	layer III, .WAV, .BWF	32, 44.1, 48, 48.048, 88.2, 96, 9.096, 176.4, 192	16, 24	both	1.65×7.58× 4.41	2.2	2 mic/line XLR w/ phantom, 2 TA3 line, AES-3 XLR, AES-3ID BNC	AES-3ID BNC	onboard battery, 10Vdc to 18Vdc	headphone jack, 10- second record buffer, Firewire
	744T	internal HD, PCMCIA	40GB HD	1	layer III, .WAV, .BWF	32, 44.1, 48, 48.048, 88.2, 96, 9.096, 176.4, 192	16, 24	1, 2 or 4 channel s	1.65×7.58× 4.41	2.3	2 mic/line XLR w/ phantom, 2 AES-3 XLR, 2 AES-3ID BNC	2 AES-3ID BNC	onboard battery, 10Vdc to 18Vdc	headphone jack, 10- second record buffer, Firewire
Tascam http://www.tascam.com														
	DA-P1	DAT	120 mins	1	PCM	32, 44.1, 48	16	stereo	10.2×2.125 ×7.375	2.6	2 mic/line XLR w/ phantom, stereo RCA, S/PDIF RCA	stereo RCA, S/PDIF RCA	battery pack, ac adapter	headphone jack